

# Nylon Cable Ties 尼龍扎綫帶

Cable Ties & Cable Tie Accessories

## Double Locking Cable Ties 雙扣式扎綫帶

#### Description

These cable ties are 'outside serated', presenting a smooth surface to the cable bundle and avoiding any problems with damage to the insulation, the width of the ties gives a broad contact area with the cable, again minimising the risk of damage. The 'Low Profile' design of the head allows for use in applications with restricted space.

Material: UL94V-2 approved PA 6.6

#### Application


Designed primarily for use within the electrical supply industry these ties are particularly useful in areas with limited space, e.g. cable bundling in shafts and are particularly suitable for outdoor use











#### Available Size

Part No. 货号	Item Code 型 号	Length 长度	Width 宽度	Mini Tensile Strength 最小拉力	Maxi Bundle Diameter 最大捆扎范围
		mm	mm	<b>lbs</b> Kg	mm
5910	Q190H-DL	190	9.0	<b>88</b> 39	62
5911	Q270H-DL	270	9.0	<b>110</b> 48	62
5912	Q360H-DL	360	9.0	<b>110</b> 48	90

### Ladder Cable Ties 梯形扎綫帶

## Description


Designed for short-term bundling at a stronger strength, bar-locking ladder cable ties are typically used in light duty applications for fastening. They are also more flexible and lightweight than standard cable ties. Identify your needs and apply bar-locking ladder cable ties for lightweight and flexible bundles.

- Bar-locking cable ties are ideal for coding, attaching I.D. plates, etc.
- Head can be locked between any two bars to allow for multiple lengths.
- Cable ties for lightweight and flexible bundles.









#### Available Size

Part No. 货号	Item Code 型 号	Length 长度	Width 宽度	Maxi Bundle Diameter 最大捆扎范围	Mini Tensile Strength 最小拉力
		mm	mm	mm	<b>lbs</b> Kg
5980	Q300I-LT	300	4.0	44.5	18 8



## Cable Tie Installation Tools 扎帶槍

 $This tool \ features \ an \ incremental \ tension-adjustment \ dial, \ a \ tension-adjustment \ indicator,$ and an automatic cut-off blade.

The tension adjustment regulates the amount of tension applied to the cable tie before the tie is cut. The adjustment is made by turning the adjustment dial until the indicator displays the desired setting.

Part No.: LS-600A

Select the proper tools and find more cable tie tools, pls see Page 19

